221 Pine St. Canby, Oregon 97013 (503) 263-4281

## FIRE DEPARTMENT EMERGENCY RESPONSE VEHICLE ACCESS AND WATER SUPPLY WORKSHEET

## THIS SECTION IS MEANT TO SERVE AS INFORMATION IN THE COMPLETION OF THE WORKSHEET

Residential, Commercial, and Agricultural structures shall provide reliable water and sufficient access to responding emergency vehicles. This code requirement falls under the Authority Having Jurisdiction (AHJ) being the Canby Fire District (CFD). Fire & Life Safety is afforded to all within the State of Oregon, and Access & Water Supply is the minimum that needs to be obtained prior to any construction project. Access and Water Supply review and approval are required **during** the Land Development stage and addressed **before** construction within the Fire District can begin. Canby Fire District has weight, length, height, width, and elevation requirements for their emergency vehicles.

Water is the tool of choice for fighting fires. Firefighters require a reliable source of water for firefighting activities that protect them from fire, support life rescue operations, minimize property losses, and protects the community from fire spread. Reliable water sources are normally in the form of fire hydrants; however, some projects are outside of a municipal water grid. In support of allowing structures out of reach from the grid, the fire department allows for a source of water to be established on the property to supply the firefighters and equipment, for a minimum amount of time, based upon the location and size of the fire area. Well water can be used to supply the amount of water required even though their gallons per minute is insufficient to supply firefighting equipment directly.

This water supply is required for the entire life of the structure, or until a reliable water source or grid becomes available near-by.

All projects receive an access and water supply review, in which requirements may be made by the local Fire Authority. Alternate Methods and Materials (AM&M) may be submitted to the local Fire Official for consideration. AM&M's for planned community developments will require the Fire Official's approval during building permit plans review. Make sure all AM&M's affecting the building plans are reflected accurately and included in the building design phase. Any changes to the project after the plans review has been completed must be resubmitted and reviewed for compliance and approval by the Fire Official.

When filling out the worksheet, please be thorough with the requested information as the information will aid the Fire Official in the access and water supply review of the project. Each project is reviewed independently and is in no way precedent-setting on future projects. Please consult your local Fire Official if you have any questions. Please include the following documents with this worksheet:

- A site plan that clearly identifies road width and segment lengths (as applicable), grades, turnout(s) as applicable, turnaround(s) as applicable, and location of any bridge/culvert.
- A floor plan for the dwelling indicating total sq. ft. of living area, covered porch(es) or deck(s), attached garage/shop, attic/basement, etc. If using a separation wall, indicate proposed location(s) and specifications.
- Attach additional sheets if necessary.

## FIRE AUTHORITY NOTES/CONDITIONS:



Fire	Official	LISE	Onlv
1110	Official	USE	OHID

Project number:

Date:



ACCESS AND WATER SUPPLY WORKSHEET

	SOLLER MORVSUIRE I		
APPLICANT INFORMATION	PERMIT INFORMATION		
NAME:	TAX LOT		
MAILING ADDRESS: CITY/STATE/ZIP:	NUMBER:		
PHONE NUMBER:	PROJECT ADDRESS:		
EMAIL ADDRESS:			
Fire Area-The total area that can be affected by fire. Fire Area includes: living space, covered porches and decks, attached garage/shop, and basement and/or attic space if capable of storage or future living area.			
NEW CONSTRUCTION N∕A □	ADDITION/REMODEL N/A		
LIVING AREA:SQFT	EXISTING FIRE AREA:SQFT		
COVERED PORCH OR DECK:SQFT	NEW LIVING AREA:SQFT		
GARAGE/SHOP (ATTACHED):SQFT	NEW COVERED PORCH OR DECK:SQFT		
OTHER SPACE (ATTIC/BASEMENT):SQFT	NEW GARAGE/SHOP (ATTACHED):SQFT		
TOTAL FIRE AREA:SQFT	NEW OTHER SPACE (ATTIC/BASEMENT):SQFT		
ACCESS	UPDATED FIRE AREA:SQFT		
NUMBER OF BUILDINGS ON ACCESS:	BUILDING INFORMATION		
APPROACH IS 8 PERCENT OR LESS YES NO	Building Construction Type-The type of framing or support members		
WIDTH:FT (MIN PER AHJ:FT)	Building Construction Types:		
LENGTH:FT HEIGHT:FT	1-Fire Resistive 2-Non-Combustible		
GRADE:% (As measured at 25' increments)	3-Ordinary (Masonry) 4-Heavy Timber		
GRADE:% (As measured at 25' increments)  TURN OUTS REQ'D_(>400')? YES NO	3-Ordinary (Masonry) 4-Heavy Timber 5-Wood Framed (Typical Residential Home)		
TURN OUTS REQ'D (>400')? YES NO 75,000 # LOAD ROCK? PAVED?	5-Wood Framed (Typical Residential Home)  BUILDING CONSTRUCTION TYPE:		
TURN OUTS REQ'D (>400')? YES NO 75,000 # LOAD ROCK? PAVED? TURN AROUND WITHIN 50FT OF THE BUILDING	5-Wood Framed (Typical Residential Home)  BUILDING CONSTRUCTION TYPE:  OTHER BUILDINGS CLOSER THAN 50FT? YES NO		
TURN OUTS REQ'D (>400')? YES NO 75,000 # LOAD ROCK? PAVED? TURN AROUND WITHIN 50FT OF THE BUILDING YES NO N/A	5-Wood Framed (Typical Residential Home)  BUILDING CONSTRUCTION TYPE:		
TURN OUTS REQ'D (>400')? YES NO 75,000 # LOAD ROCK? PAVED? TURN AROUND WITHIN 50FT OF THE BUILDING YES NO N/A TURN AROUND DESIGN	5-Wood Framed (Typical Residential Home)  BUILDING CONSTRUCTION TYPE: OTHER BUILDINGS CLOSER THAN 50FT? YES NO IF YES: USE? CU FT: BUILDING HEIGHT TO THE PEAK: FT BUILDING HEIGHT TO THE EAVES: FT.		
TURN OUTS REQ'D (>400')? YES NO 75,000 # LOAD ROCK? PAVED? TURN AROUND WITHIN 50FT OF THE BUILDING YES NO N/A	5-Wood Framed (Typical Residential Home)  BUILDING CONSTRUCTION TYPE: OTHER BUILDINGS CLOSER THAN 50FT? YES NO  IF YES: USE? CU FT: BUILDING HEIGHT TO THE PEAK: FT  BUILDING HEIGHT TO THE EAVES: FT.  CEILING HEIGHT: FT. ATTIC HEIGHT: FT.		
TURN OUTS REQ'D (>400')? YES NO 75,000 # LOAD ROCK? PAVED? TURN AROUND WITHIN 50FT OF THE BUILDING YES NO N/A TURN AROUND DESIGN  TURN AROUND DESIGN  Y T MOD T CULDESAC LOOP	5-Wood Framed (Typical Residential Home)  BUILDING CONSTRUCTION TYPE: OTHER BUILDINGS CLOSER THAN 50FT? YES NO IF YES: USE? CU FT: BUILDING HEIGHT TO THE PEAK: FT BUILDING HEIGHT TO THE EAVES: FT.		
TURN OUTS REQ'D (>400')? YES NO 75,000 # LOAD ROCK? PAVED? TURN AROUND WITHIN 50FT OF THE BUILDING YES NO N/A TURN AROUND DESIGN	5-Wood Framed (Typical Residential Home)  BUILDING CONSTRUCTION TYPE: OTHER BUILDINGS CLOSER THAN 50FT? YES NO  IF YES: USE? CU FT: BUILDING HEIGHT TO THE PEAK: FT  BUILDING HEIGHT TO THE EAVES: FT.  CEILING HEIGHT: FT. ATTIC HEIGHT: FT.  ATTIC TYPE: STANDARD GAMBREL/MANSARD		
TURN OUTS REQ'D (>400')? YES NO 75,000 # LOAD ROCK? PAVED? TURN AROUND WITHIN 50FT OF THE BUILDING YES NO N/A TURN AROUND DESIGN  TURN AROUND DESIGN  Y T MOD T CULDESAC LOOP  IS THERE A BRIDGE OR CULVERT WITHIN THE ACCESS?  NO YES Oregon Engineer #:	5-Wood Framed (Typical Residential Home)  BUILDING CONSTRUCTION TYPE: OTHER BUILDINGS CLOSER THAN 50FT? YES NO  IF YES: USE? CU FT: BUILDING HEIGHT TO THE PEAK: FT  BUILDING HEIGHT TO THE EAVES: FT.  CEILING HEIGHT: FT. ATTIC HEIGHT: FT.  ATTIC TYPE: STANDARD GAMBREL/MANSARD  RESIDENTIAL FIRE SPRINKLERS PROPOSED IN BUILDING		
TURN OUTS REQ'D (>400')? YES NO 75,000 # LOAD ROCK? PAVED? TURN AROUND WITHIN 50FT OF THE BUILDING YES NO N/A TURN AROUND DESIGN  TURN AROUND DESIGN  Y T MOD T CULDESAC LOOP  IS THERE A BRIDGE OR CULVERT WITHIN THE ACCESS?  NO YES Oregon Engineer #:	BUILDING CONSTRUCTION TYPE: OTHER BUILDINGS CLOSER THAN 50FT? YES NO FY YES: USE? BUILDING HEIGHT TO THE PEAK: BUILDING HEIGHT TO THE EAVES: CEILING HEIGHT: FT. ATTIC TYPE: STANDARD GAMBREL/MANSARD RESIDENTIAL FIRE SPRINKLERS PROPOSED IN BUILDING PLAN? YES NO		